



MOTOTRBO™ SL4010e

YOU'RE SMARTER, CONNECTED

With this dynamic evolution of MOTOTRBO digital two-way radios, you're smarter, better connected and more productive. The SL4010e is designed for the manager who needs complete control. With a slim and light form factor incorporating high performance integrated voice and data, this next-generation radio delivers smart connectivity to your organisation.

SMART

The MOTOTRBO SL4010e is an ETSI DMR Standards compliant slim and light portable radio that connects you with sophistication. Pocket-sized and with a smooth outline, the radio features a full keypad and 5-line colour screen with a customisable display scheme. The built-in vibrate function alerts you quietly when you need to be discreet, and a comprehensive range of audio accessories allows you to stay connected without disturbing your customers.

CONNECTED

With integrated voice and data, the SL4010e delivers operation critical communications. Bluetooth® lets you talk without wires, while also enabling precise indoor location-tracking. Powerful audio and advanced noise cancellation ensure your call is heard, even in noisy environments, and 280-character text messaging simplifies complex communications. Integrated Wi-Fi® enables remote software updates, minimising downtime and keeping you connected.

PRODUCTIVE

With a clear user interface designed to support productivity applications such as Work Order Ticketing, the SL4010e helps your staff make the most of their work day. Voice Announcement and Text-to-Speech allow users to monitor radio settings and text communications hands-free, while sophisticated scan functions keep you in touch with many teams at once.





Model Number	SL4010e
Band	UHF Band 1
GENERAL SPECIFICATIONS	
Frequency	403-470 MHz
High Power Output	3 W
Low Power Output	1 W
Channel Spacing	12.5 kHz
Channel Capacity	1000
Li-ion 2300mAh Battery	
Dimensions with Radio (H x W x D)	121 x 55 x 23 mm
Weight with Radio	174 g
Battery Life¹	14.3 hrs
Power Supply (Nominal)	3.7 (Nominal)

KEY FEATURES OF THE SL4010e RADIO

- Integrated accelerometer for optional Man Down
- Bluetooth® 4.0
- Indoor location tracking
- Integrated Wi-Fi
- Over-the-air software updates
- Upgraded audio for greater clarity at high volume
- Improved expandability
- Increased transmitter power, for greater range
- Selectable power levels

TRANSMITTER SPECIFICATIONS

4FSK Digital Modulation	12.5 kHz Data: 7K60F1D and 7K60FXD
	12.5 kHz Voice: 7K60F1E and 7K60FXE
	Combination of 12.5 kHz Voice and Data: 7K60F1W
Digital Protocol	ETSI TS 102 361-1, -2, -3 DMR Tier II & Tier III
Conducted/Radiated Emissions (TIA603D)	-36 dBm < 1GHz, -30 dBm > 1GHz
Frequency Stability	± 1.5 ppm

RECEIVER SPECIFICATIONS

Digital Sensitivity (5% BER)	0.15 uV
Conducted Spurious Emissions (TIA603D)	-57 dBm

AUDIO SPECIFICATIONS

Digital Vocoder Type	AMBE+2™
Audio Response	TIA603D
Rated Audio	0.5 W
Audio Distortion at Rated Audio	3%

BLUETOOTH SPECIFICATIONS

Version	4.0
Range	Class 2, 10 m
Supported Profiles	Bluetooth Headset Profile (HSP) Serial Port Profile (SPP) Motorola Solutions fast push-to-talk
Simultaneous Connections	1 x audio accessory and 1 x data device
Permanent Discoverable Mode	Optional

Wi-Fi SPECIFICATIONS

Standards Supported	IEEE 802.11b, 802.11g, 802.11n
Security Protocol Supported	WPA, WPA-2, WEP
Maximum Number of SSIDs	128

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature²	-20 °C to +60 °C
Storage Temperature²	-30 °C to +70 °C
Electrostatic Discharge	IEC 61000-4-2 Level 3
Dust and Water Intrusion	IEC 60529 - IP54
Salt Fog	5% NaCl for 8 hrs at 35 C, 16 hrs standing
Packaging Test	MIL-STD 810D and E

¹ Typical battery life, 5/5/90 profile at maximum transmitter power with Bluetooth, Wi-Fi and Option Board applications disabled. 1370mAh battery rating is for 2W output.

Actual observed runtimes may vary.

² Radio only. Battery operation down to -10°C only.

• Standard feature

○ Optional feature

CONNECTION

- UHF Band, 3 W
- Colour Screen
- Full Keypad
- 1000 Channels
- Digital Only
- Voice and Data
- Integrated Wi-Fi
- Canned Text Messaging
- Freeform Text Messaging
- Work Order Ticketing
- Bluetooth Audio
- Bluetooth Data
- Bluetooth Permanent Discoverable Mode
- Bluetooth Indoor Location Tracking
- Voice Announcement
- Text to Speech
- Option Board SL4010e
- Home Channel Reminder
- Vibrate Alert
- Ambient Light Sensor

AUDIO

- Intelligent Audio
- SINC+ Noise Cancellation
- Acoustic Feedback Suppressor
- Microphone Distortion Control
- User-Selectable Audio Profiles
- Switch Speaker
- Trill Enhancement

PERSONALISATION

- Wide Range of Accessories
- 2 Programmable Buttons
- Emergency Button

MANAGEMENT

- Radio Management
- Over-the-Air Programming
 - Over-the-Air Software Update

SAFETY

- Integrated Accelerometer
- Man Down
- Lone Worker
- Basic Privacy
- Enhanced Privacy
 - AES256 Encryption
- Transmit Interrupt (decode)
- Transmit Interrupt (encode)
- Digital Emergency
- Emergency Search Tone
- Remote Monitor
- Radio Disable / Enable
- Rated to IP54
- Rugged to MIL-STD 810

SYSTEMS

- Direct Mode (including Dual Capacity Direct Mode)
- IP Site Connect (Single and Multi-Site)
- Capacity Plus (Single and Multi-Site)
 - Capacity Max

MILITARY STANDARDS

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temp	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.5	I/A1, II/A1
Low Temp	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II/C1
Temp Shock	503.1	I	503.2	A1/C3	503.3	A1/C3	503.4	I	503.5	I-C
Solar Radiation	505.1	II	505.2	I/Hot-Dry	505.3	I/Hot-Dry	505.4	I/Hot-Dry	505.5	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III
Dust	510.1	I, II	510.2	I, II	510.3	I, II	510.4	I, II	510.5	I, II
Vibration	514.2	VIII/F, W, XI	514.3	I/10, II/3	514.4	I/24, II/5	514.5	I/24, II/5	514.6	I/24, II/5
Shock	516.2	I, II	516.3	I, IV	516.4	I, IV	516.5	I, IV	516.6	I, IV


BLUETOOTH

Connect to your radio without wires, for extra comfort and safety. A full portfolio of Bluetooth headsets and earpieces is available.



COVERT ACCESSORIES

When you need to stay in touch discreetly, choose from our range of covert audio accessories. From clear tube earpieces to virtually invisible wireless in-ear units.




ENERGY SOLUTIONS

Make sure your radio is powered and charged properly, with our range of energy solutions. Choose from single and multi-unit chargers, and slim and high capacity batteries.



EARPIECES

For all-day comfort, choose from our range of earpieces. Lightweight or heavy duty, discreet or rugged, with or without built-in hearing protection.



CARRY SOLUTIONS

However you choose to carry your SL4010e, we have a solution available. For example, the secure plastic holster protects the radio while keeping it easily to hand.



RSMs

Make sending and receiving messages even easier with a Remote Speaker Microphone designed specifically for the SL range.



To discover how to be smartly connected, visit www.motorolasolutions.com/mototrbo or find your closest Motorola representative or authorised Partner at www.motorolasolutions.com/contactus

Motorola Solutions Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB, United Kingdom.

Availability is subject to individual country law and regulations. All specifications shown are typical unless otherwise stated and are subject to change without notice.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license.

All other trademarks are the property of their respective owners. ©2020 Motorola Solutions, Inc. All rights reserved. (04-20)



MOTOROLA SOLUTIONS