



making waves in a wire
-free world

Wireless Panic Button

Low-Power UHF radio transmitter with
key-switch reset



Transmit to pager and/or fixed receivers

Fixed Panic Button

Designed for wall or under-desk mounting, the panic transmitter sends a repeating signal when activated until it is reset with a key. The button flashes periodically to indicate that it is in its triggered state.

Multiple units can be used on a site, each sending its own unique identifier to the receiving devices, which could be pagers, fixed receivers or a combination of both.

UHF SRD radio transmitter with a range of up to approximately 200 metres (dependant on site conditions)

Power is provided by a standard 9V battery.

Compliance:

CFR47 Part 90. FCC ID: JRNUSAWAVETRACK
EN 300 220, EN 301 489



SPECIFICATIONS

Power:	9V battery
Current:	Transmit: <50mA @ 10mW Sleep Mode: <20 uA
Operating Temp:	-30 to +50 deg C
Tx Frequency Range:	430 - 470 MHz
Tx Power:	10mW max
Channel Spacing:	12.5KHz @ 2.5 KHz deviation
Tx Baud:	512 / 1200
Protocol:	POCSAG
Footprint:	60 (W) x 80 (L) x 43 (D) mm (excluding tabs)



Scope Communications UK Ltd
Quantum House
Steamer Quay
Totnes, Devon, TQ9 5AL
England

Tel: +44 (0) 1803 860700
Fax: +44 (0) 1803 863716
Web: www.scope-uk.com
Email: sales@scope-uk.com